

DEUTZ® BAIHUA-DEUTZ SERIES DIESEL GENERATOR SETS



Model		KBD-20	KBD-24	KBD-30	KBD-40	KBD-50	KBD-75	KBD-108	KBD-120			
ENGINE	Model	D226B-3	D226B-3	TD226B-3	TD226B-4	TD226B-4	TD226B-6	TBD226B-6	TBD226B-6			
	Rated output (kw)	30	30	45	45	60	90	120	132			
	Governing method	Mechanical										
	Intaking method	Natural aspirated				Turbocharged						
	Grease-box Volume(L)	7.25					13					
	Cylinder numbers	3			4		6					
	Oil-box Volume(L)	64										
	Fuel Consumption(g/kw.h)	239		228		221		227		216		
	Cooling Starting Method	Closed water cooled/electric starting										
GENERATOR	Model	KB-20	KB-24	KB-30	KB-40	KB-50	KB-75	KB-108	KB-120			
	Rated output (kw)	20	24	30	40	50	75	108	120			
	Rated Current(A)	36.1	43.3	54.1	72.2	90.2	135.3	194.9	216.5			
	Rated Voltage(V)	400/230										
	Frequency(HZ)	50/60										
	Power Factor(COSφ)	0.8lagging										
	Phase / Connection	3-phase 4-wire				Y type connection						
	Excitation	Harmonic OR brushless Excitation										
	Voltage Regulation	Manual Automatic										
Net Weight(kg)	710		760		800		860		1230	1290	1350	
Packing size LWH(cm)	1680x700x1500			1900x788x1200		1950x788x1400		1950x788x1400		2200x788x1450		2400x788x1450