

**Perkins** **BAIHUA-Perkins**  
SERIES DIESEL GENERATOR SETS



Model	KBP-36	KBP-56	KBP-75	KBP-80	KBP-110	
Rated Power(KW)	36/40	56/60	72/80	80/90	108/120	
ENGINE	Model	1004G	1004TG	1006TG1A	1006TG2A	1006TAG
	Rated output (kw)	45	60	90	120	132
	Governing method	Nature aspirated		Mechanical		
	Intaking method			Turbocharged		Turbocharged intercooled
	Grease-box Volume(L)	9.5		14.3		
	Cylinder numbers	3	4	6		
	Oil-box Volume(L)	64	64	64	64	64
	Fuel Consumption(g/kw.h)	210	208	208	204	
	Cooling Starting Method	Closed water cooled/electric starting				
	Model	KB-36	KB-56	KB-75	KB-80	KB-110
GENERATOR	Rated output (kw)	40	60	80	90	120
	Rated Current(A)	65	101	135.3	144.3	198.5
	Rated Voltage(V)	220/400V				
	Frequency(HZ)	50/60 HZ				
	Power Factor(COS&)	0.8lagging				
	Phase / Connection	3-phase 4-wire		Y type connection		
	Excitation	Harmonic Excitation or phase Compound or brushless				
	Voltage Regulation	Automatic				
Net Weight(kg)	754	850	1060	1200	1450	
Packing size LWH(cm)	170x75x125	190x80x125	220x92x130	220x92x130	240x95x146	